

Digital Migration Radio PD485

- Clear Audio
- Built-in Bluetooth and GPS option
- Analogue and Digital Auto Detect





Features

- 
ANALOGUE & DIGITAL AUTO DETECT
 Compatible with analogue conventional and digital conventional modes. Allows PD485 to simultaneously monitor analogue and digital modes and automatically respond in each mode. Extremely easy migration to digital from analogue.
- 
DTMF SIGNALING
- 
DUAL CAPACITY DIRECT MODE
 In direct mode, you can have two voice calls simultaneously, because of the two timeslots from DMR TDMA technology. This feature can be used to increase the radio capacity at no extra cost, without the need for additional frequency licenses.
- 
PRIVACY (Optional)
 Basic end-to-end Encryption has your voice and data transmission secured.
- 
EMERGENCY ALARM/CALL
 Emergency Alarm can be sent to other radios via the one touch programmable button, establishing an emergency call in a specific group. Improves your emergency response time.
- 
PSEUDO TRUNK
 This virtual trunking feature allocates a free timeslot for urgent communications. This effectively enhances frequency efficiency and allows you to communicate in a timely manner in emergency situations.
- 
REAL TIME CLOCK
 Ensures the real time is displayed on the menu and GPS/messaging.
- 
RADIO REGISTRATION SERVICE
 RRS allows the PD485 to communicate with Smart Dispatch and SmartOne, so that the dispatcher can check if the radio is on or offline.
- 
SUPPLEMENTARY FEATURES (Optional)
 The PD485 can provide radio enable/disable, remote monitor and priority interrupt as optional features.
- 
ROAMING (Optional)
 Roam from each repeater site to have a non-stop voice transmission.
- 
GPS POSITIONING (Factory Optional)
 The built-in GPS module and GPS antenna are designed for outdoor positioning, making it the ideal tool to support location based requirements.
- 
BUILT-IN BLUETOOTH (Factory Optional)
 Built-in Bluetooth supports PD485 wireless audio accessories and other Bluetooth transmissions.
- 
RELIABLE AND DURABLE
 The PD485 is compliant with Mil-STD-810 G and IP54.
- 
VOX
 This feature allows you to activate the radio microphone at speaking volume, so that you do not need to press the PTT.

Target Markets



FLEET MANAGEMENT

With RRS, the PD485 can be accessed by dispatch applications for effective radio fleet management. Whether it's voice dispatching, SDS messaging or location based services, the PD485 is ideal for team communications.



COMMERCIAL

Clear digital voice processors and powerful audio output ensures you receive your transmission even in noisy environments. Use the wireless earpiece or other audio accessories to improve your operating experience.



SECURITY

Privacy in any voice or data communication is essential for security teams. Emergency call, priority interrupt and remote monitor functions provide a reliable communication system to support security staff who always need to remain alert and connected.



OUTDOOR ADVENTURES

Flexible to program through the front panel and built to military standards, achieving IP54 rating for water and dust ingress protection, the PD485 is ready for your next adventure.

Standard



Li-ion Battery
(2000mAh)
BL2010



Belt Clip
BC19



General MCU Rapid-rate Charger
(for Li-Ion/Ni-MH Batteries)
CH10A07



Stubby Antenna



Switching Power Adapter



Hand Strap


Options



EHM19
C Style Earloop Earpiece
with On-MK PTT



EAM12
Detachable Transparent
Acoustic Tube Earpiece
with PTT&MIC
cable



EAM13
2-wire Surveillance
Earpiece with VOX &
Transparent Acoustic
Tube (Black)



EHM20
Swivel Earpiece with
PTT&MIC cable



ESM12
Earbud with On-MK
PTT and VOX
switch



Antenna



MCA08
MCU Multi-unit Rapid
rate Charger



CH10A06
Dual Pocket MCU Charger Kit
(for Li-Ion/Ni-MH Batteries)
(charger + power supply
cable)



SM26M1
Remote Speaker
Microphone without
emergency button
(IP54)



PC76
Data Programming
Cable



LCY015
Nylon Carrying
Jacket



Specifications

General		
Frequency Range		UHF: 350-470MHz VHF: 136-174MHz
Channel Capacity		256
Zone Capacity		16
Channel Spacing		25/12.5KHz
Operating Voltage		7.4V
Battery		2000mAh (Li-Ion)
Battery Life (5/5/90)		Analogue/Digital: 12/16 hours
Weight		308g
Dimensions		117×55×37mm
Frequency Stability		±0.5ppm
Antenna Impedance		50Ω
Receiver		
Sensitivity (Digital)		0.22μV / BER 5%
Sensitivity (Analog)		0.22μV (Typical) (12dB SIN AD) 0.4μV (20dB SIN AD) 0.22μV (12dB SIN AD)
Adjacent Selectivity	TIA-603	60dB @ 12.5KHz/70dB @ 25KHz
	ETSI	60dB @ 12.5KHz/70dB @ 25KHz
Spurious Response Rejection	TIA-603	70dB @ 12.5/25KHz
	ETSI	70dB @ 12.5/25KHz
Inter-modulation	TIA-603	70dB @ 12.5/25KHz
	ETSI	65dB @ 12.5/25KHz
Hum & Noise		40dB @ 12.5KHz 45dB @ 25KHz
Rated Audio Power Output		0.5W
Rated Audio Distortion		≤3%
Audio Response		+1 ~ -3dB
Conducted Spurious Emission		<-57dBm

Transmitter	
RF Power Output	VHF High power: 5W VHF Low power: 1W UHF High power: 4W UHF Low power: 1W
FM Modulation	11K0F3E @ 12.5KHz 16K0F3E @ 25KHz
4FSK Digital Modulation	12.5KHz Data Only: 7K60FXD 12.5KHz Data & Voice: 7K60FXW
Conducted/Radiated Emission	-36dBm <1GHz, -30dBm >1GHz
Modulation Limiting	±2.5KHz @ 12.5KHz ±5.0KHz @ 25KHz
FM Hum & Noise	40dB @ 12.5KHz 45dB @ 25KHz
Adjacent Channel Power	60dB @ 12.5KHz, 70dB @25KHz
Audio Response	+1 ~ -3dB
Audio Distortion	≤3%
Digital Vocoder Type	AMBE++
Digital Protocol	ETSI-TS102 361-1,-2,-3
Environmental	
Operating Temperature	-30°C~ +60°C
Storage Temperature	-40°C~ +85°C
ESD	IEC 61000-4-2 (Level 4) ±8kV (Contact) ±15kV (Air)
Dustproof & Waterproof	IP54 Standard
Humidity	Per MIL-STD-810 G Standard
Shock & Vibration	Per MIL-STD-810 G Standard

PD48X, X=0, 2, 5, 6 or 8, model number varies geographically. For details, please contact our regional sales representatives.

All specifications are subject to change without notice due to continuous development.